ELECTRIC GREASE PUMPS Mod. DC12V "Mec-Grease"

MAX PRESSURE = 360bar DELIVERY = 750 g/min

Art. 010-2020-012 Electric grease pump Mod. DC12V For standard drums 18-30 kg (shank length 480 mm) Polyurethane seals

Art. 010-2050-012 Electric grease pump Mod. DC12V For standard drums 50-60 kg (shank length 750 mm) Polyurethane seals

Art. 010-2200-012 Electric grease pump Mod. DC12V For standard drums 180-220 kg (shank length 950 mm) Polyurethane seals


MECLUBE	Kg	m³	Nº M
010-2020-012	12,300	0,045	1
010-2050-012	13,300	0,056	1
010-2200-012	14,000	0,067	1

Technical data		010-2020-012	010-2050-012	010-2200-012
Voltage	Volt	12	12	12
Electricity	А	25	25	25
Max pressure	bar	360	360	360
Grease outlet connection	BSP	F 1/4" G	F 1/4" G	F 1/4" G
Grease delivery capacity	g/min	750	750	750
Shank diameter	mm	30	30	30
Shank length	mm	480	750	950
For drums with capacity of	kg	18-30	50-60	180-220



Mec-Grease

tric Grease Pump



These pumps are suitable for the supply at high pressure of greases with viscosity up to NLGI 2 at short and long distances. The working pressure of the grease pumps here is 360 bar with a flow rate of 750 g/min.

