



**024-1244-G00**

**Art. 024-1244-G00**

**High delivery oil dispensing nozzle**  
Flow rate 90 l/min max press. 100 bar  
Composed by:  
Aluminium handle with F 3/4" swivel joint  
Button to block the lever  
**Flexible end M 3/4"**  
Semiautomatic drop valve Ø 35 mm



**024-1244-H00**

**Art. 024-1244-H00**

**High delivery oil dispensing nozzle**  
Flow rate 90 l/min max press. 100 bar  
Composed by:  
Aluminium handle with F 3/4" swivel joint  
Button to block the lever  
**Rigid end 30°**  
Semiautomatic drop valve Ø 35 mm



**024-1245-G00**

**Art. 024-1245-G00**

**High delivery oil digital dispensing nozzle**  
Flow rate 60 l/min max press. 70 bar  
Composed by:  
Oil digital flow meter (Art.024-1245-005)  
Rubber protection  
Aluminium handle with F 3/4" swivel joint  
**Flexible end M 3/4"**  
Semiautomatic drop valve Ø 35 mm



**024-1245-H00**

**Art. 024-1245-H00**

**High delivery oil digital dispensing nozzle**  
Flow rate 60 l/min max press. 70 bar  
Composed by:  
Oil digital flow meter (Art.024-1245-005)  
Rubber protection  
Aluminium handle with F 3/4" swivel joint  
**Rigid end 30°**  
Semiautomatic drop valve Ø 35 mm



**024-1245-005**

**Art. 024-1245-005**

**High delivery oil digital flow meter**  
It is equipped with two displays, one for partial measures (resettable) to 5 digits and one for total measures (not resettable) to 8 digits of the dispensed fluid

**FEATURES**

- Easy calibration
- Double totalizer
- Electronic reset
- High precision
- Ergonomic grip
- Lever block is included
- Low battery consumption
- Different units of measurements can be selected: litres, pints, quarts or gallons.
- Not approved for public usage

Technical Data	024-1245-005
Inlet/outlet connection	F 3/4" BSP
Pressure min/max	0,35 - 70 bar
Flow min/max	6 - 60 l/min
Temperature	-10° + 50° C
Accuracy	+/- 0,5%
Lithium battery	2 x 1,5V AAA