

MANUAL OIL DISPENSERS



027-1320-000



027-1322-000



027-1326-000



027-1328-000

Art. 027-1320-000

16 I manual oil dispenser Composed by: Tank capacity 16 I Manual pump Delivery hose 2,0 m length With level valve, rigid end 30° Flow rate: 80cc for each stroke



16 I wheeled manual oil dispenser

Art. 027-1322-000

Delivery hose 2,0 m length With level valve, rigid end 30° Flow rate: 80cc for each stroke

/Kg


027-1322-000 11,900 0,090

m³

1

Composed by: Tank capacity 16 I Manual pump







E റ്റ

28 cm 45 cm

Art. 027-1326-000 24 I manual oil dispenser Composed by: Tank capacity 24 I (with level indicator) Double-acting manual pump Oil dispensing nozzle with flexible hose and drop valve (Art.024-1232-F00) Delivery hose 2,0 m length Flow rate: 80cc for each stroke



027-1326-000 14,300 0,074 1

Art. 027-1328-000 50 I manual oil dispenser Composed by: Tank capacity 50 I (with level indicator) Double-acting manual pump Oil dispensing nozzle with flexible hose and drop valve (Art.024-1232-F00) Delivery hose 2,0 m length Flow rate: 80cc for each stroke /Kg m³

43 cm 47 cm

Manual oil dispensers with double-acting manual pump, suitable for high viscosity oils (SAE 15-220). They are advised for the filling or dispensing of motor oils, transmissions, differential gears, hydraulic power packs and so on.

027-1328-000 26,200 0,196