



040-1430-000


## Art. 040-1430-000

### Air-operated oil suction-drainer for exhausted oil 65 l

Tank capacity 65 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 15 l  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art.044-1479-000)



040-1430-000 30,400 0,240 1



040-1432-000


## Art. 040-1432-000

### Air-operated oil suction-drainer for exhausted oil 90 l

Tank capacity 90 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 20 l  
with ergonomic and 360° swivelling abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art.044-1479-000)



040-1432-000 37,400 0,240 1



040-1433-000


## Art. 040-1433-000

### Air-operated oil suction-drainer for exhausted oil 120 l

Tank capacity 120 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 20 l  
with ergonomic and 360° swivelling abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art. 044-1479-000)



040-1433-000 38,700 0,310 1



Technical data		040-1430-000	040-1432-000	040-1433-000
Air pressure for depressurisation	bar	7,5 - 8	7,5 - 8	7,5 - 8
Depressurisation time	l/min	2' - 2,5'	2,5' - 3'	3' - 3,5'
Max suction capacity with a depressurisation	l	43 - 45	60 - 65	85 - 90
Suction time with Ø 6 and oil at 60 - 80 °C temperature	l/min	1,5 - 2	1,5 - 2	1,5 - 2
Suction hose-emptying - hose length	m	2	2	2

The air-operated oil aspirators are ideal for a rapid changing of motor oil to every vehicle. The recovery of the exhausted oil is carried out for fall, through the lateral basin adjustable for height, and also through aspiration thanks to the probes.

After depressurization they work autonomously, without the need to be connected to compressed air, for an independent and quick aspiration, using the suitable probe between the included kit of 10 probes.

The units can suction till 2/3 of their capacity.

**Change the oil at a temperature of 60° - 80° C (when the engine is just switched off).**

**Warning:** do not use these units for the suction of brake oils, fuels and inflammable liquids




## Art. 040-1442-000

**Air-operated suction-drainer for exhausted oil 65 l with pre-chamber**

Tank capacity 65 l with level indicator  
Abs tool holder basin with 3 sections  
Pre-chamber capacity 10 l  
Recovery basin capacity 15 l  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art.044-1479-000)



040-1442-000 35,200 0,290 2




## Art. 040-1445-000

**Air-operated suction-drainer for exhausted oil 90 l with pre-chamber**

Tank capacity 90 l with level indicator  
Abs tool holder basin with 3 sections  
Pre-chamber capacity 10 l  
Recovery basin capacity 20 l  
with ergonomic and **360° swivelling** abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art.044-1479-000)



040-1445-000 42,300 0,290 2




## Art. 040-1448-000

**Air-operated suction-drainer for exhausted oil 120 l with pre-chamber**

Tank capacity 120 l with level indicator  
Abs tool holder basin with 3 sections  
Pre-chamber capacity 10 l  
Recovery basin capacity 20 l  
with ergonomic and **360° swivelling** abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)  
Equipped with 10 standard probes (Art.044-1479-000)



040-1448-000 43,800 0,360 2



Technical data		040-1442-000	040-1445-000	040-1448-000
Air pressure for depressurisation	bar	7,5 - 8	7,5 - 8	7,5 - 8
Depressurisation time	l/min	2' - 2,5'	2,5' - 3'	3' - 3,5'
Max suction capacity with a depressurisation	l	43 - 45	60 - 65	85 - 90
Suction time with Ø 6 and oil at 60 - 80 °C temperature	l/min	1,5 - 2	1,5 - 2	1,5 - 2
Suction hose-emptying - hose length	m	2	2	2

The air-operated oil aspirators are ideal for a rapid changing of motor oil to every vehicle. The recovery of the exhausted oil is carried out for fall, through the lateral basin adjustable for height, and also through aspiration thanks to the probes.

After depressurization they work autonomously, without the need to be connected to compressed air, for an independent and quick aspiration, using the suitable probe between the included kit of 10 probes.

The units can suction till 2/3 of their capacity.

**The pre-chamber permits the immediate control of quantity and quality of the aspirated oil, it is equipped with a device for the internal cleaning.**

**Change the oil at a temperature of 60° - 80 °C (when the engine is just switched off).**

**Warning:** do not use these units for the suction of brake oils, fuels and inflammable liquids



045-1462-000


## Art. 045-1462-000

### Exhausted oil drain unit 65 l

Tank capacity 65 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 15 l  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)



045-1462-000 26,900 0,220 1



## Art. 045-1460-000


### Exhausted oil drain unit 90 l

Tank capacity 90 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 20 l  
with ergonomic and **360° swivelling** abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)



045-1460-000 33,500 0,240 2

045-1460-E00 29,500 0,240 1



045-1460-000

## Art. 045-1460-E00

### Exhausted oil drain unit 90 l

Composed like Art.045-1460-000 but with:  
Recovery basin capacity 15 l




045-1465-000 33,800 0,310 2

## Art. 045-1465-000

### Exhausted oil drain unit 120 l

Tank capacity 120 l with level indicator  
Abs tool holder basin with 3 sections  
Recovery basin capacity 20 l  
with ergonomic and **360° swivelling** abs funnel  
with breakwater grate to drip the substituted oil filters  
Pneumatic air emptying (max pressure 0,5 bar)



045-1465-000

Technical data		045-1462-000	045-1460-000	045-1460-E00	045-1465-000
Basin dimensions	mm	ø 450	760X705	ø 450	760X705
Minimum height	mm	1000	1200	1200	1200
Maximum height	mm	1700	1850	1850	1850
Emptying hose length	mm	2	2	2	2

For the recovery by fall of exhausted oil of the engine, the transmission and the differential of motor-vehicles on lifts.

The basin is equipped with a grate of support to drip the substituted filters, and it can be regulated according to the height.

**Warning:** It is not possible to recovery brake oils, fuels, inflammable and corrosive liquids.