

World's 1st Rechargeable Battery Operated Pump. Designed for pumping fuels, water based media, light oils, DEF & select chemicals from metal drums & IBC / Totes

Compact & lightweight construction

Convenient ON/OFF switch with LED indicator

Built-in fuse for overload protection

Silenced motor makes almost no noise

Telescopic suction tube extends from 33-1/2" (850 mm) to 49" (1245 mm) for use with 205 litre (55 gallon) drums or 275-330 gallon (1000-1250 litre) IBC / Totes

Stainless steel filter built into the suction tube inlet prevents contaminants from getting in & causing damage

Built-in 2" bung adaptor fits directly on 205 litre (55 gallon) metal drums. Bung adapter can be adjusted by 0.6" (15 mm) to adjust to drums with varying heights

Includes an additional bung thread converter for converting 2" standard bung threads to 2.5" x 5 mm buttress for using pump with IBC / Totes

Supplied complete with 2m (6.6') hose & manual dispensing nozzle with 3/4" (19 mm) OD Stainless Steel Spout

Duty Cycle

15 minutes ON / 15 Minutes OFF

WETTED COMPONENTS

Viton, POM, Stainless Steel, PE, NBR, PP









RECOMMENDED USE

Diesel, Kerosene, Bio Diesel, DEF, Adblue, Water based media, Antifreeze, Detergents, Light oils with viscosity upto 100 cst

NOT TO USE WITH

Gasoline, Corrosive chemicals, Lacquer thinners, any material that is not compatible with the pump construction

FLUIDS

DIESEL	DEF / ADBLUE	WATER	KEROSENE
			
DETERGENTS	ANTIFREEZE	PESICIDES & HERBICIDES	LIGHT OIL
			

3/4" (19 mm)
SS spout

Lift handle

19.2V, 1.5Ah
Ni cd/18.5V,
1.3Ah Li-ion
battery

Thread converter
(With 2.5 x 5 mm
Buttress threads)

Telescopic
suction tube

SS strainer

55.5 mm

EDR/55T/RB/19N/US

On/off switch

Pump outlet with
swivel connection

Manual
dispensing
nozzle

Flexible
corrugated hose
2m (6.6') long

Nozzle
Holster

SPECIFICATIONS

MOTOR TYPE	DC Brush Motor (5 Pole)
DC POWER CABLE	4m long with Crocodile Clips
AC POWER ADAPTER	Input: 100 to 240 V AC, 50 / 60 Hz, Output: 12 V DC Constant Voltage, 3A max
RECHARGEABLE BATTERY	19.2V, 1.5 Ah Ni Cd Battery/ 18.5V, 1.3Ah Li-Ion Rechargeable Battery
MAX. VISCOSITY OF MEDIA	100 cst
TEMPERATURE	5° to 40°C (41° to 104°F)



AVAILABLE IN 3 CONFIGURATIONS



With 12V DC
Power Cable



With 100V-240V, 50/60 Hz
AC Dual Voltage
Power Adaptor



With a choice of 19.2V, 1.5Ah
Ni Cd Battery/18.5V, 1.3Ah Li-Ion
Rechargeable Battery
& 1hr Battery Charger

ORDERING INFORMATION

CAT NR.	ORD NR.	DESCRIPTION	FLOW RATE (UPTO)		BOX QTY.
			(LPM)	(GPM)	
★ EDR/55T/DC	45503	Electric Drum Pump with DC Power Cable (12V)	18.4	4.86	4
EDR/55T/AC/US	45504	Electric Drum Pump with UL Listed AC Power Adapter, US Socket	18.9	5	4
EDR/55T/AC/EU	45505	Electric Drum Pump with CE AC Power Adapter, European Socket	18.9	5	4
EDR/55T/AC/AU	45506	Electric Drum Pump with AC Power Adapter, AU Socket	18.9	5	4
EDR/55T/AC/UK	45517	Electric Drum Pump with AC Power Adapter, UK Socket	18.9	5	4
★ EDR/55T/RB/19N/US	45507	Electric Drum Pump with Battery Adapter, one 19.2V, 1.5 Ah Ni Cd Rechargeable battery & UL Listed Battery Charger, US Socket	28	7.4	4
EDR/55T/RB/19N/EU	45508	Electric Drum Pump with Battery Adapter, one 19.2V, 1.5 Ah Ni Cd Rechargeable battery & CE Battery Charger, EU Socket	28	7.4	4
EDR/55T/RB/19N/AU	45509	Electric Drum Pump with Battery Adapter, one 19.2V, 1.5 Ah Ni Cd Rechargeable battery & Battery Charger, AU Socket	28	7.4	4
EDR/55T/RB/19N/UK	45518	Electric Drum Pump with Battery Adapter, one 19.2V, 1.5 Ah Ni Cd Rechargeable battery & Battery Charger, UK Socket	28	7.4	4
◆ EDR/55T/RB/19L/US	45516	Electric Drum Pump with Battery Adapter, one 18.5V, 1.3 Ah Li-Ion Rechargeable battery & Battery Charger, US Socket	28	7.4	4
◆ EDR/55T/RB19L/EU	45515	Electric Drum Pump with Battery Adapter, one 18.5V, 1.3 Ah Li-Ion Rechargeable battery & Battery Charger, EU Socket	28	7.4	4
◆ EDR/55T/RB/19L/UK	45519	Electric Drum Pump with Battery Adapter, one 18.5V, 1.3 Ah Li-Ion Rechargeable battery & Battery Charger, UK Socket	28	7.4	4

★ Best Seller ◆ New