
## FGP Food Grade Precleaner

# **USDA Certified Precleaner Meets Highest Standards for Food Processing Applications**

The FGP Food Grade Precleaner from Flexco is easy to install, easy to maintain, and disassembles in a snap for regular cleaning and sanitization. The FGP Precleaner works on any belt from 4" to 60" (100 mm to 1500 mm) and the blade is available in both white, blue, and metal detectable gray FDA approved food grade material.



### Features and Benefits:

- Minimal hardware so installation, tensioning, and blade replacement are easy.
- **Simple design** with stainless steel components and food grade materials limit crevices and opportunities for bacteria growth.
- **Easily tensioned** to minimize blade wear, eliminate belt damage, and maximize cleanability.
- **Optional** metal detectable gray blade for additional protection against food contamination.
- Available in standard blade widths for belts from 12" to 60" (300 mm to 1500 mm). Blades can be cut down to appropriate length.
- Compatible with endless as well as mechanical splices.
- Suitable for use on modular belting.





# FDA Approved, USDA Certified

Designed to meet the strict sanitary guidelines established for food processing operations, the FGP Precleaner is made of FDA approved materials. It has been certified by the United States Department of Agriculture for use with meat and poultry, as well as dairy, for facilities requiring USDA accepted equipment in their operations.



# Disassembly in Less than a Minute

The FPG Precleaner has been designed for quick disassembly and reassembly. Simply

- Snap off the blade
- Remove the tensioning bolt
- Pull out the tensioning device
- Pull out the pole and bushings

and in less than a minute the FPG is disassembled for cleaning and sanitization.

Reassembly is just as quick so your line is up and running again fast.




### **FGP** Food Grade Precleaner

#### **Specifications:**

- Temperature Range -20°F to 140°F (-29°C to 60°C)
- Blade Height 3.0" (76 mm)
- Blade Width Range 4" - 60" (102-1524 mm)
- Blade Hardness 80D Shore Hardness
- Pulley Diameter Range 2" (50 mm) to 10.5" (267 mm)
- Pole/Mounting Material 304 Stainless Steel

• Blade Material Food-grade UHMW or UHMW with Stainless Steel



Pole Length Specifications										
Pole Length*		Minimum Blade Width		Maxi Blade		Maximum Conveyor structure width at cleaner mounting location				
in.	mm	in.	mm	in.	mm	in.	mm			
24	610	4	102	12	305	22	556			
30	813	4	102	18	457	28	708			
36	965	18	457	24	610	34	861			
42	1067	18	457	30	813	40	1013			
48	1219	30	813	36	965	46	1165			
54	1372	30	813	42	1067	52	1318			
60	1524	30	813	48	1219	58	1470			
66	1676	30	813	54	1372	64	1623			
72	1829	30	813	60	1524	70	1775			

<sup>\*</sup>Pole length = blade length + 12" on standard cleaners.

#### How to choose the correct size blade for your conveyor.

- 1. Measure your belt width.
- 2. Choose the Blade Width that corresponds to your belt width.
- 3. Measure your conveyor width.
- 4. Verify the Maximum Conveyor Width shown in the selection chart is larger than your conveyor width. If your conveyor width is smaller than the maximum width shown, choose the next larger blade width that accommodates your conveyor width.
- 5. Blade and/or pole can be cut to users required length. Pole must be 2" longer than the outside width of conveyor structure at the mounting location.

FGF	FGP Food Grade Precleaner											
Blade Conveyor Width Width		veyor	Weight		White Blade		Blue Blade		Gray Metal Detectable Blade			
in.	mm	in.	mm	lbs.	kg.	Ordering Number	Item Code	Ordering Number	Item Code	Ordering Number	Item Code	
12	305	22	559	6.7	3.0	FGP-W3-12	56009	FGP-BL3-12	56000	FGP-MD3-12	56027	
18	457	28	711	7.7	3.5	FGP-W3-18	56010	FGP-BL3-18	56001	FGP-MD3-18	56028	
24	610	34	864	8.6	3.9	FGP-W3-24	56011	FGP-BL3-24	56002	FGP-MD3-24	56029	
30	762	40	1016	9.5	4.3	FGP-W3-30	56012	FGP-BL3-30	56003	FGP-MD3-30	56030	
36	914	46	1168	10.5	4.8	FGP-W3-36	56013	FGP-BL3-36	56004	FGP-MD3-36	56031	
42	1067	52	1321	11.5	5.2	FGP-W3-42	56014	FGP-BL3-42	56005	FGP-MD3-42	56032	
48	1219	58	1473	12.4	5.6	FGP-W3-48	56015	FGP-BL3-48	56006	FGP-MD3-48	56033	
54	1372	64	1626	13.3	6.0	FGP-W3-54	56016	FGP-BL3-54	56007	FGP-MD3-54	56034	
60	1524	70	1778	14.2	6.4	FGP-W3-60	56017	FGP-BL3-60	56008	FGP-MD3-60	56035	

